

Pathrider™ 10

STYLISH DESIGN & PREMIUM
PERFORMANCE AT AN
EXCELLENT VALUE.


PATHRIDER™ 10

The sleek, sporty **Pathrider™ 10** scooter delivers high performance operation, all-new features and feather-touch disassembly. With a full complement of advanced standard features exclusive low-profile, puncture-proof tyres, back-lit battery gauge, and wraparound easy drive tiller, the Pathrider 10 is a greater value than ever before.



Pathrider™ 10	4-wheel scooter
Weight capacity:	159 kg (350 lbs.)
Maximum speed ¹ :	Up to 8.5 km/h (5 mph)
Ground clearance ² :	5 cm (2")
Turning radius:	157.5 cm (62")
Overall length ² :	119 cm (47")
Overall width ² :	56.5 cm (22")
Tyre size:	Front & Rear: 9 cm x 25 cm (3.5" x 10") (puncture-proof)
Range per charge ¹ :	Up to 40 km (25 miles)
Maximum obstacle climbing ability:	5 cm (2")
Total Weight Without Batteries:	63.5 kg (140 lbs.)
Heaviest piece when disassembled:	32 kg (71 lbs.)
Standard seating:	Type: Foldable molded plastic Weight: 13 kg (28 lbs.) Material: Black Vinyl Dimensions: 46 cm (18") width 43 cm (17") depth
Drive System:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System:	Electronic, regenerative, and electromechanical
Battery Requirements ³ :	Two 12-volt, deep cycle Size: 35 AH (standard) or 40 AH (optional) Weight: 35 AH: 15 kg (32.5 lbs.) each; 40 AH: 15 kg (32.5 lbs.) each
Battery Charger:	3-amp, off-board

Colour:



Features

- Exclusive one-hand feather-touch disassembly provides the ultimate quick transport system
- Auto-connecting front-to-rear harness
- Easy drive tiller with wrap-around handles
- Pride's exclusive stylish, light weight, low profile, non-scuffing, puncture-proof wheels
- New back-lit LED battery meter for increased accuracy and visibility in any setting
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination
- Lightweight, molded plastic seat with viscoelastic foam inserts for increased comfort
- Includes pinchless hinges & eight-position seat rotation
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port for standard dual voltage off-board charger

Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder

¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or Gel-Cell type required.

NOTE: All specifications subject to change without notice.


"The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice".

"Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement".

21 Healey Rd.
Dandenong, Victoria 3175
www.pridemobility.com

ACN 088 609 661 ABN 66 088 609 661

Tel: 03 9706 4611
Fax: 03 9706 4622



Pride
Mobility Products
Australia Pty Ltd